

```

*****;
** Program Name : adsl-demo-7d-peds-eval-eff.sas          **;
** Date Created : 15Nov2021                                **;
** Programmer Name : (b) (4), (b) (6)                      **;
** Purpose       : Create adsl-demo-7d-peds-eval-eff      **;
** Input data    : adsl, adc19ef                          **;
** Output file   : adsl-demo-7d-peds-eval-eff.html        **;
*****;
options mprint mlogic symbolgen nocenter missing=" ";
ods escapechar="~";
proc datasets library=WORK kill nolist nodetails;
quit;

**Setup the environment**;
%let
bprot=/Volumes/app/cdars/prod/sites/cdars4/prjC459/nda2_unblinded_esub/sbla1215_esub_adam/saseng/cdisc3_0/;
%let
prot=/Volumes/app/cdars/prod/sites/cdars4/prjC459/nda2_unblinded_esub/sbla1215_esub_adam/saseng/cdisc3_0/analysis/eSUB;
%let codename=adsl-demo-7d-peds-eval-eff;
libname datvprot "&bprot.data_vai" access=readonly;
%let outlog=&prot./logs/&codename..log;
%let outtable=&prot./output/&codename..html;

proc printto log="&outlog." new;
run;

*****;
* Clean *;
*****;

proc delete data=work._all_;
run;

proc format;
value sex 1='Male' 2='Female';
value ethnic 1='Hispanic/Latino' 2='Non-Hispanic/non-Latino' 3='Not reported'
      4='Unknown';
value crace 1="White" 2="Black or African American" 2.5="All others"
      3="(*ESC*){nbspace 5}American Indian or Alaska Native"
      4="(*ESC*){nbspace 5}Asian"
      5="(*ESC*){nbspace 5}Native Hawaiian or other Pacific Islander"
      6="(*ESC*){nbspace 5}Multiracial" 7="(*ESC*){nbspace 5}Not reported"
      8="(*ESC*){nbspace 5}Unknown";
run;

proc sort data=datvprot.adsl out=adsl;
   by usbjid;
run;

proc sort data=datvprot.adc19ef out=adc19ef(keep=usbjid PDSDMFL VRBLNGFL
                                             CRD1NGFL PDP17FL PDP27FL) nodupkey;

```

```

by usubjid;
run;

data adsl;
merge adsl(in=a) adc19ef;
by usubjid;

if a;
run;

data adsl;
set adsl(in=a);
by usubjid;

if a;
length covblstx COMBODFLX OBSCATFL $50.;

if covblst="POS" then
do;
covblstx="Positive(*ESC*){super e}";
covblstnx=1;
end;
else if covblst="NEG" then
do;
covblstx="Negative(*ESC*){super f}";
covblstnx=2;
end;
else if covblst not in ("POS" "NEG") then
do;
covblstx="Unknown";
covblstnx=3;
end;

if COMBODFL='Y' or /*(bmicatn = 4 and age >=16) or*/
OBESEFL="Y" then
do;
COMBODFLNX=1;
COMBODFLX="Yes";
end;
else
/* if COMBODFL='N' then */
do;
COMBODFLNX=2;
COMBODFLX="No";
end;

if /*(bmicatn = 4 and AGETR01 >=16) or*/
OBESEFL="Y" then
do;
OBSCATFN=1;
OBSCATFL="Yes";
end;
else

```

```
do;
    OBSCATFN=2;
    OBSCATFL="No";
end;
```

```
if racialdn=999 then
    racialdn=.;
```

```
run;
```

```
data adsl;
    set adsl;
    length countryx $50;
```

```
if country='ARG' then
    countryx='Argentina';
else if country='BRA' then
    countryx='Brazil';
else if country='DEU' then
    countryx='Germany';
else if country='TUR' then
    countryx='Turkey';
else if country='USA' then
    countryx='USA';
else if country='ZAF' then
    countryx='South Africa';
else
    countryx='Others';
```

```
run;
```

```
data race_ao;
    set adsl;
```

```
if aracen not in (1, 2);
aracen=2.5;
arace="ALL OTHERS";
AGETR01=.;
run;
```

```
data adsl;
    set adsl race_ao;
run;
```

```
data adsl;
    set adsl;
    length agegr1x $50.;
```

```
if 12<=age<=15 then
    do;
        agegr1nx=1;
        agegr1x="12 to 15 ";
    end;
```

```
if 16<=age<=55 then
    do;
```

```

agegr1nx=2;
agegr1x="16 to 55 ";
end;

if age>55 then
do;
agegr1nx=3;
agegr1x="(*ESC*){Unicode 003E}55 ";
end;
run;

data agp1;
set adsl;

if 16<=age<=17;
agegr1nx=5;
agegr1x="16 to 17 ";
AGETR01=.;
run;

data agp2;
set adsl;

if 16<=age<=25;
agegr1nx=6;
agegr1x="16 to 25 ";
AGETR01=.;
run;

data agp3;
set adsl;

if 16<=age<=64;
agegr1nx=7;
agegr1x="16 to 64 ";
AGETR01=.;
run;

data agp4;
set adsl;

if 18<=age<=64;
agegr1nx=8;
agegr1x="18 to 64 ";
AGETR01=.;
run;

data agp5;
set adsl;

if 55<=age<=64;
agegr1nx=9;
agegr1x="55 to 64 ";
AGETR01=.;

```

```

run;

data agp7;
  set adsl;

  if age>=65;
  agegr1nx=4;
  agegr1x="(*ESC*){unicode 2265}65 ";
  AGETR01=.:;

run;

data agp8;
  set adsl;

  if 65<=age<=74;
  agegr1nx=10;
  agegr1x="65 to 74 ";
  AGETR01=.:;

run;

data agp9;
  set adsl;

  if age>=75;
  agegr1nx=11;
  agegr1x="(*ESC*){unicode 2265}75 ";
  AGETR01=.:;

run;

data agp10;
  set adsl;

  if 75<=age<=85;
  agegr1nx=12;
  agegr1x="75 to 85 ";
  AGETR01=.:;

run;

data agp11;
  set adsl;

  if age>85;
  agegr1nx=13;
  agegr1x="(*ESC*){Unicode 003E}85 ";
  AGETR01=.:;

run;

data adsl;
  set adsl agp1 agp2 agp3 agp4 agp5 agp7 agp8 agp9 agp10 agp11;
run;

data g_adsl_dsin;
  set adsl;
  where EVALEFFL="Y" and PDP27FL='Y' and agegr1n=1 and phasen ne 1;

```

```

run;

data __trtmap;
length trtcode trtdecd $100;

if 0 then
    set g_adsl_dsin(keep=TRT01PN);
trtval=1;

if vtype(TRT01PN)='C' then
    trtcode=tranwrd(compbl(quote("8")), ' ', " ");
else
    trtcode="8";
trtdecd="BNT162b2 (30 (*ESC*){unicode 03BC}g)";
trtvar="TRT01PN";
trtbl="TRT01P";
output;
trtval=2;

if vtype(TRT01PN)='C' then
    trtcode=tranwrd(compbl(quote("9")), ' ', " ");
else
    trtcode="9";
trtdecd="Placebo";
trtvar="TRT01PN";
trtbl="TRT01P";
output;
trtval=3;

if vtype(TRT01PN)='C' then
    trtcode=tranwrd(compbl(quote("8 9")), ' ', " ");
else
    trtcode="8 9";
trtdecd="Total";
trtvar="TRT01PN";
trtbl="TRT01P";
output;
stop;

run;

data g_adsl_dsin;
set g_adsl_dsin;

if TRT01PN in (8) then
    do;
        newtrtn=1;
        newtrt=coalesce("BNT162b2 (30 (*ESC*){unicode 03BC}g)", TRT01P);
        output;
    end;

if TRT01PN in (9) then
    do;
        newtrtn=2;
        newtrt=coalesce("Placebo", TRT01P);

```

```

        output;
      end;

      if TRT01PN in (8 9) then
        do;
          newtrtn=3;
          newtrt=coalescec("Total", TRT01P);
          output;
        end;
      run;

*-----;
* Initialize dataset for non-pvalue footnote queue. ;
*-----;

data _stdft1(compress=no);
  length model $200 mark $5;
  index=0;
  model=' ';
  mark=' ';
run;

*-----;
* Initialize dataset for pvalue related footnote queue. ;
*-----;

data _stdft2(compress=no);
  length model $200 mark $5;
  index=0;
  model=' ';
  mark=' ';
run;

*-----;
* Initialize structure for _BASETEMPLATE dataset. ;
*-----;

data _basetemplate(compress=no);
  length _varname $8 _cvalue $35 _direct $20 _vrlabel $200 _rwlable
    _colabel $800 _datatyp $5 _module $8 _pr_lbl $ 200;
  array _c _character_;
  delete;
run;

*-----;
* Create next _DATAn dataset ;
*-----;

data _data1;
  set g_adsl_dsin;
  where (NEWTRTN is not missing);
run;

proc sql noprint;

```

```

select put(nobs - delobs, 12.) into :_nobs from dictionary.tables
      where (libname="WORK" and memname="_DATA1");
select setting into :miss from dictionary.options where
      upcase(optname)="MISSING";
quit;

*-----;
* Count number of treatment groups ;
*-----;

proc sql noprint;
  select count(unique NEWTRTN) into :_trtn from _data1 where NEWTRTN is not
    missing;
quit;

*-----;
* Generate variable _TRT. Use assigned order if applicable ;
*-----;

proc sort data=_data1;
  by NEWTRTN USUBJID;
run;

data _data1;
  retain _trt 0;
  length _str $200;
  _datasrt=1;
  set _data1 end=eof;
  by NEWTRTN USUBJID;
  drop _str;
  _str=' ';
  _lastby=1;
  _dummyby=0;

if first.NEWTRTN then
  do;
    if not missing(NEWTRTN) then
      do;
        _trt=_trt + 1;
        end;
      *-----;
      * Generate _STR as the treatment label ;
      *-----;
      _str=NEWTRT;
      *-----;
      * Update _TRTLB&n with generated treatment label ;
      *-----;

      if _trt > 0 then
        call symput('_trtlb'||compress(put(_trt, 4.)), trim(left(_str)));
    end;
  run;

```

```

*-----;
* Count number of patients in each treatment. ;
*-----;

proc sql noprint;
  select compress(put(count(*), 5.) ) into :_trt1 - :_trt3 from (select distinct
    USUBJID, _trt from _data1 where NEWTRTN is not missing) group by _trt;
  select compress(put(count(*), 5.) ) into :_trt4 from (select distinct USUBJID
    from _data1 where NEWTRTN is not missing);
quit;

*-----;
* Generate a dataset containing all by-variables ;
*-----;

proc sort data=_data1 out=_bydat1(keep=_datasrt _dummyby) nodupkey;
  by _datasrt;
run;

data _bydat1;
  set _bydat1 end=eof;
  by _datasrt;
  retain _preby 0;
  drop _preby;
  _byvar1=0;

  if eof then
    do;
      call symput("_preby1", compress(put(_byvar1, 4.)));
      if 0=0 then
        output;
    end;
run;

data _bydat1;
  set _bydat1;
  by _datasrt;
  length _bycol _byindnt $50 _bylast $10;
  _bycol="";
  _byindnt="";
  _bylast="";
run;

proc sort data=_bydat1;
  by _datasrt;
run;

proc sort data=_data1 out=_data1;
  by _datasrt;
run;

data _null_;
  set _data1 end=eof;

```

```

if eof then
    call symput('dptlab', vlabel(SEXN));
run;

data _anal1;
length SEXN 8;
set _data1;

if SEXN=. then
    SEXN=9998;
    _blkssrt=1;
    _cnt=1;
    _cat=1;

    if _trt <=0 then
        delete;
    output;
run;

proc sort data=_anal1;
    by _datasrt _blkssrt SEXN _trt _cat;
run;

*--- Counts for each by-sequence, dependant var, and treatment combination ---*;

data _temp1;
    set _anal1;
    output;
run;

proc sort data=_temp1 out=_temp91 nodupkey;
    by _datasrt _blkssrt _cat SEXN _trt USUBJID;
run;

proc freq data=_temp91;
    format SEXN;
    tables _datasrt*_blkssrt*_cat * SEXN * _trt / sparse norow nocol nopercent
        out=_pct1(drop=percent);
run;

proc sort data=_anal1 out=_denom1(keep=_datasrt _cat) nodupkey;
    by _datasrt _cat;
run;

data _denom1;
    set _denom1;
    by _datasrt _cat;
    label count='count';
    _trt=1;
    count=&_trt1;
    output;
    _trt=2;
    count=&_trt2;

```

```

output;
_trt=3;
count=&_trt3;
output;
run;

*-----;
* Create _DENOMF a frame dataset for the denominators ;
*-----;

data _denomf1;
.datasrt=1;
set _bydat1(keep=);
* All treatment groups ;
_trt1=0;
_trt2=0;
_trt3=0;
* _CAT is the subgroup variable ;
_cat=1;
output;
run;

*-----;
* Transpose _DENOM into _DENOMIN to get COUNT as _TRTn columns ;
*-----;

proc sql noprint;
select put(nobs - delobs, 12.) into :_nobs from dictionary.tables
  where (libname="WORK" and memname="_DENOM1");
select setting into :miss from dictionary.options where
  upcase(optname)="MISSING";
quit;

proc transpose data=_denom1 out=_denomin1(drop=_name__label_) prefix=_trt;
  by _datasrt _cat;
  var count;
  id _trt;
run;

*-----;
* VALRANGE=FULL. Create full rank categories WITHOUT using where. ;
*-----;

proc sql noprint;
select count(distinct SEXN) into :totexpv from _anal1;
select distinct SEXN into :expv1 - :expv2 from _anal1 order by SEXN;
quit;

*-----;
* Create _FRAME dataset using all combinations of category variable ;
*-----;

data _frame1;
.datasrt=1;

```

```

set _bydat1(keep=);
  _blkssrt=1;
length SEXN 8;
  _catLabl=" ";
  _trt=1;
SEXN=1;
  _catord=1;
  _cat=1;
output;
  _trt=2;
SEXN=1;
  _catord=1;
  _cat=1;
output;
  _trt=3;
SEXN=1;
  _catord=1;
  _cat=1;
output;
  _catLabl=" ";
  _trt=1;
SEXN=2;
  _catord=2;
  _cat=1;
output;
  _trt=2;
SEXN=2;
  _catord=2;
  _cat=1;
output;
  _trt=3;
SEXN=2;
  _catord=2;
  _cat=1;
output;
run;

*-----;
* Merge the _PCT dataset with its frameup dataset(_FRAME) ;
*-----;

proc sort data=_frame1;
  by _datasrt _blkssrt _cat SEXN _trt;
run;

proc sort data=_pct1;
  by _datasrt _blkssrt _cat SEXN _trt;
run;

data _pct1;
  merge _frame1(in=_inframe) _pct1;
  by _datasrt _blkssrt _cat SEXN _trt;
  if _inframe;

```

```

if count=. then
    count=0;
run;

*-----;
* Delete Zero filled MISSING category rows for each combination of;
* _datasrt & _byvar _blkrsrt;
*-----;

proc sort data=_pct1;
    by _datasrt _blkrsrt SEXN;
run;

data _miss1(keep=_datasrt _blkrsrt SEXN totcount);
    set _pct1;
    where SEXN=9998;
    retain totcount;
    by _datasrt _blkrsrt SEXN;

    if first.SEXN then
        totcount=0;
    totcount=totcount+count;

    if last.SEXN;
run;

data _pct1(drop=totcount);
    merge _pct1 _miss1;
    by _datasrt _blkrsrt SEXN;

    if totcount=0 then
        delete;
run;

*****;
*IF PCTDISP=CAT/DPTVAR then add dptvar into denomitor frame dataset;
*****;
*-----;
* Merge the _DENOMIN with its frame up dataset (_denomf) ;
*-----;

proc sort data=_denomf1;
    by _datasrt _cat;
run;

proc sort data=_denomin1;
    by _datasrt _cat;
run;

data _denomin1;
    merge _denomf1(in=_inframe) _denomin1;
    by _datasrt _cat;

```

```

if _inframe;
  _blkssrt=1;
run;

*-----;
* Merge in _PCT(counts) with the _DENOMIN(denominator for percents) ;
*-----;

proc sort data=_pct1;
  by _datasrt_cat;
run;

*-----;
* Create _VARNAME variable to hold depend variable name. ;
* Create _VRLABEL variable to display Group label. ;
* Create _RWLABEL variable to display &dptvar categories. ;
*-----;

data _pct1;
  if 0 then
    set _basetemplate;
  merge _denomin1(in=_a) _pct1;
  by _datasrt_cat;

  if _a;
  _varname="SEXN ";
  _vrlabel="Sex ";
  _rwlable=put(SEXN, sex.);

  if SEXN=9998 then
    do;
      _rwlable="Unknown ";
      _catord=9998;
    end;
  else if SEXN=9999 then
    do;
      _rwlable="Total ";
      _catord=9999;
    end;
  if _catord=. then
    _catord=9997;
run;

proc sort data=_pct1;
  by _datasrt _blkssrt _catord SEXN _trt _cat;
run;

*-----;
* Create _CVALUE variable to display results. ;
* Create _ROWSRT variable to order results. ;
*-----;

data _base1;

```

```

length _catlabl $200;
set _pct1 end=eof;
by _datasrt _blkssrt _catord SEXN _trt _cat;
retain _rowsrt 0 _rowmax 0;
array _trtcnt(*) _trt1-_trt4;
drop _rowmax _cpct;
length _cpct $100;
_cpct='';
_module='mcatstat';

if count > . then
    _cvalue=put(count, 5.);
else
    _cvalue=put(0, 5.);
*-----;
* Format percent to append to display value in _CVALUE ;
*-----;

if _trt ne . then
    do;

        if _trtcnt(_trt) > 0 then
            do;
                percent=count / _trtcnt(_trt) * 100;

                if percent > 0 then
                    do;

                        if round(percent, 0.1) GE 0.1 then
                            _cpct="(*ESC*){nbspace 1}("||strip(put(percent, 5.1))||")";
                        else
                            _cpct="(*ESC*){nbspace 1}(0.0)";
                        _cvalue=trim(_cvalue)||_cpct;
                    end;
                end;
            end;
        end;

if length(_cvalue) < 13 then
    do;
        *-----;
        * Put character A0x at right most character to pad text;
        *-----;
        substr(_cvalue, 13, 1)='A0'x;
    end;

if first.SEXN then
    do;
        _rowsrt=_rowsrt + 1;
        _rowmax=max(_rowsrt, _rowmax);
    end;
_datatyp='data';
_indent=0;
_dptindt=0;
_vorder=1;

```

```

_rowjump=1;

if upcase(_rwlable)='NONE' then
  _rwlable=' ';
  _indent=3;
  _dptindt=0;

if _trt=3 +1 then
  _trt=9999;

if eof then
  call symput('_rowsrt', compress(put(_rowmax, 4.)));
  _direct="TOP ";
  _p=2;
run;

data _null_;
  set _data1 end=eof;

  if eof then
    call symput('dptlab', vlabel(ARACEN));
run;

data _anal2;
  length ARACEN 8;
  set _data1;
  where same and ARACEN is not missing;
  _blktsrt=2;
  _cnt=1;
  _cat=1;

  if _trt <=0 then
    delete;
  output;
run;

proc sort data=_anal2;
  by _datasrt _blktsrt ARACEN _trt _cat;
run;

*--- Counts for each by-sequence, dependant var, and treatment combination ---*;

data _temp2;
  set _anal2;
  output;
run;

proc sort data=_temp2 out=_temp92 nodupkey;
  by _datasrt _blktsrt _cat ARACEN _trt USUBJID;
run;

proc freq data=_temp92;
  format ARACEN;
  tables _datasrt*_blktsrt*_cat * ARACEN * _trt / sparse norow nocol nopercnt

```

```

        out=_pct2(drop=percent);
run;

proc sort data=_anal2 out=_denom2(keep=_datasrt _cat) nodupkey;
    by _datasrt _cat;
run;

data _denom2;
    set _denom2;
    by _datasrt _cat;
    label count='count';
    _trt=1;
    count=&_trt1;
    output;
    _trt=2;
    count=&_trt2;
    output;
    _trt=3;
    count=&_trt3;
    output;
run;

*-----;
* Create _DENOMF a frame dataset for the denominators ;
*-----;

data _denomf2;
    _datasrt=1;
    set _bydat1(keep=);
    * All treatment groups ;
    _trt1=0;
    _trt2=0;
    _trt3=0;
    * _CAT is the subgroup variable ;
    _cat=1;
    output;
run;

*-----;
* Transpose _DENOM into _DENOMIN to get COUNT as _TRTn columns ;
*-----;

proc sql noprint;
    select put(nobs - delobs, 12.) into :_nobs from dictionary.tables
        where (libname="WORK" and memname="_DENOM2");
    select setting into :miss from dictionary.options where
        upcase(optname)="MISSING";
quit;

proc transpose data=_denom2 out=_denomin2(drop=_name__label_) prefix=_trt;
    by _datasrt _cat;
    var count;
    id _trt;
run;

```

```

*-----;
* Create _FRAME dataset using all combinations of category variable ;
*-----;

data _frame2;
  _datasrt=1;
  set _bydat1(keep=);
  _blkssrt=2;
  length ARACEN 8;
  _catLabl=" ";
  _trt=1;
  ARACEN=1;
  _catord=1;
  _cat=1;
  output;
  _trt=2;
  ARACEN=1;
  _catord=1;
  _cat=1;
  output;
  _trt=3;
  ARACEN=1;
  _catord=1;
  _cat=1;
  output;
  _catLabl=" ";
  _trt=1;
  ARACEN=2;
  _catord=2;
  _cat=1;
  output;
  _trt=2;
  ARACEN=2;
  _catord=2;
  _cat=1;
  output;
  _trt=3;
  ARACEN=2;
  _catord=2;
  _cat=1;
  output;
  _catLabl=" ";
  _trt=1;
  ARACEN=2.5;
  _catord=3;
  _cat=1;
  output;
  _trt=2;
  ARACEN=2.5;
  _catord=3;
  _cat=1;
  output;
  _trt=3;

```

```
ARACEN=2.5;
_catord=3;
_cat=1;
output;
_catLabl=" ";
_trt=1;
ARACEN=3;
_catord=4;
_cat=1;
output;
_trt=2;
ARACEN=3;
_catord=4;
_cat=1;
output;
_trt=3;
ARACEN=3;
_catord=4;
_cat=1;
output;
_catLabl=" ";
_trt=1;
ARACEN=4;
_catord=5;
_cat=1;
output;
_trt=2;
ARACEN=4;
_catord=5;
_cat=1;
output;
_trt=3;
ARACEN=4;
_catord=5;
_cat=1;
output;
_catLabl=" ";
_trt=1;
ARACEN=5;
_catord=6;
_cat=1;
output;
_trt=2;
ARACEN=5;
_catord=6;
_cat=1;
output;
_trt=3;
ARACEN=5;
_catord=6;
_cat=1;
output;
_catLabl=" ";
_trt=1;
```

```

ARACEN=6;
_catord=7;
_cat=1;
output;
_trt=2;
ARACEN=6;
_catord=7;
_cat=1;
output;
_trt=3;
ARACEN=6;
_catord=7;
_cat=1;
output;
_catLabl=" ";
_trt=1;
ARACEN=7;
_catord=8;
_cat=1;
output;
_trt=2;
ARACEN=7;
_catord=8;
_cat=1;
output;
_trt=3;
ARACEN=7;
_catord=8;
_cat=1;
output;
run;

*-----;
* Merge the _PCT dataset with its frameup dataset(_FRAME) ;
*-----;

proc sort data=_frame2;
   by _datasrt _blkssrt _cat ARACEN _trt;
run;

proc sort data=_pct2;
   by _datasrt _blkssrt _cat ARACEN _trt;
run;

data _pct2;
   merge _frame2(in=_inframe) _pct2;
   by _datasrt _blkssrt _cat ARACEN _trt;
   if _inframe;
   if count=. then
      count=0;
run;

```

```

*-----;
* Delete Zero filled MISSING category rows for each combination of;
* _datasrt & _byvar _blcksrt;
*-----;

proc sort data=_pct2;
   by _datasrt _blcksrt ARACEN;
run;

data _miss2(keep=_datasrt _blcksrt ARACEN totcount);
   set _pct2;
   where ARACEN=9998;
   retain totcount;
   by _datasrt _blcksrt ARACEN;

   if first.ARACEN then
      totcount=0;
   totcount=totcount+count;

   if last.ARACEN;
run;

data _pct2(drop=totcount);
   merge _pct2 _miss2;
   by _datasrt _blcksrt ARACEN;

   if totcount=0 then
      delete;
run;

proc sort data=_denomf2;
   by _datasrt _cat;
run;

proc sort data=_denomin2;
   by _datasrt _cat;
run;

data _denomin2;
   merge _denomf2(in=_inframe) _denomin2;
   by _datasrt _cat;

   if _inframe;
   _blcksrt=2;
run;

*-----;
* Merge in _PCT(counts) with the _DENOMIN(denominator for percents) ;
*-----;

proc sort data=_pct2;
   by _datasrt _cat;
run;

```

```

data _pct2;
if 0 then
  set _basetemplate;
merge _denomin2(in=_a) _pct2;
by _datasrt _cat;

if _a;
  _varname="ARACEN ";
  _vrlabel="Race ";
  _rwlable=put(ARACEN, crace.);

if ARACEN=9998 then
  do;
    _rwlable="Missing ";
    _catord=9998;
  end;
else if ARACEN=9999 then
  do;
    _rwlable="Total ";
    _catord=9999;
  end;

if _catord=. then
  _catord=9997;
run;

proc sort data=_pct2;
  by _datasrt _blcksrt _catord ARACEN _trt _cat;
run;

*-----;
* Create _CVALUE variable to display results. ;
* Create _ROWSRT variable to order results. ;
*-----;

data _base2;
length _catlabl $200;
set _pct2 end=eof;
by _datasrt _blcksrt _catord ARACEN _trt _cat;
retain _rowsrt 0 _rowmax 0;
array _trtcnt(*) _trt1-_trt4;
drop _rowmax _cpct;
length _cpct $100;
_cpct='';
_module='mcatstat';

if count > . then
  _cvalue=put(count, 5.);
else
  _cvalue=put(0, 5.);
*-----;
* Format percent to append to display value in _CVALUE ;
*-----;

```

```

if _trt ne . then
  do;

    if _trtcnt(_trt) > 0 then
      do;
        percent=count / _trtcnt(_trt) * 100;

        if percent > 0 then
          do;

            if round(percent, 0.1) GE 0.1 then
              _cpct="(*ESC*){nbspace 1}("||strip(put(percent, 5.1))||")";
            else
              _cpct="(*ESC*){nbspace 1}(0.0)";
              _cvalue=trim(_cvalue)||_cpct;
            end;
          end;
        end;
      end;
    end;

if length(_cvalue) < 13 then
  do;
    *-----;
    * Put character A0x at right most character to pad text;
    *-----;
    substr(_cvalue, 13, 1)='A0'x;
  end;

if first.ARACEN then
  do;
    _rowsrt=_rowsrt + 1;
    _rowmax=max(_rowsrt, _rowmax);
  end;
_datatyp='data';
_indent=0;
_dptindt=0;
_vorder=1;
_rowjump=1;

if upcase(_rwlable)= '_NONE_ ' then
  _rwlable=' ';
  _indent=3;
  _dptindt=0;

if _trt=3 +1 then
  _trt=9999;

if eof then
  call symput('_rowsrt', compress(put(_rowmax, 4.)));
  _direct="TOP ";
  _p=2;
run;
*****;
*SPECIFICATION 5 -1) Ethnicity - n and percent *;

```

```
*****;
```

```
data _anal3;
length ETHNICN 8;
set _data1;
where same and ETHNICN is not missing;
_blkstrt=3;
_cnt=1;
_cat=1;

if _trt <=0 then
    delete;
output;
run;
```

```
proc sort data=_anal3;
    by _datasrt _blkstrt ETHNICN _trt _cat;
run;
```

```
*--- Counts for each by-sequence, dependant var, and treatment combination ---*;
```

```
data _temp3;
set _anal3;
output;
run;
```

```
proc sort data=_temp3 out=_temp93 nodupkey;
    by _datasrt _blkstrt _cat ETHNICN _trt USUBJID;
run;
```

```
proc freq data=_temp93;
format ETHNICN;
tables _datasrt*_blkstrt*_cat * ETHNICN *_trt / sparse norow nocol nopercnt
    out=_pct3(drop=percent);
run;
```

```
proc sort data=_anal3 out=_denom3(keep=_datasrt _cat) nodupkey;
    by _datasrt _cat;
run;
```

```
data _denom3;
set _denom3;
by _datasrt _cat;
label count='count';
_trt=1;
count=&_trt1;
output;
_trt=2;
count=&_trt2;
;
output;
_trt=3;
count=&_trt3;
output;
```

```

run;

*-----;
* Create _DENOMF a frame dataset for the denominators ;
*-----;

data _denomf3;
  _datasrt=1;
  set _bydat1(keep=);
  * All treatment groups ;
  _trt1=0;
  _trt2=0;
  _trt3=0;
  * _CAT is the subgroup variable ;
  _cat=1;
  output;
run;

*-----;
* Transpose _DENOM into _DENOMIN to get COUNT as _TRTn columns ;
*-----;

proc transpose data=_denom3 out=_denomin3(drop=_name__label_) prefix=_trt;
  by _datasrt _cat;
  var count;
  id _trt;
run;

*-----;
* VALRANGE=FULL. Create full rank categories WITHOUT using where. ;
*-----;

proc sql noprint;
  select count(distinct ETHNICN) into :totexpv from _anal3;
  select distinct ETHNICN into :expv1 - :expv3 from _anal3 order by ETHNICN;
quit;

*-----;
* Create _FRAME dataset using all combinations of category variable ;
*-----;

data _frame3;
  _datasrt=1;
  set _bydat1(keep=);
  _blkssrt=3;
  length ETHNICN 8;
  _catLabl=" ";
  _trt=1;
  ETHNICN=1;
  _catord=1;
  _cat=1;
  output;
  _trt=2;
  ETHNICN=1;

```

```

_catord=1;
_cat=1;
output;
_trt=3;
ETHNICN=1;
_catord=1;
_cat=1;
output;
_catLabl=" ";
_trt=1;
ETHNICN=2;
_catord=2;
_cat=1;
output;
_trt=2;
ETHNICN=2;
_catord=2;
_cat=1;
output;
_trt=3;
ETHNICN=2;
_catord=2;
_cat=1;
output;
_catLabl=" ";
_trt=1;
ETHNICN=3;
_catord=3;
_cat=1;
output;
_trt=2;
ETHNICN=3;
_catord=3;
_cat=1;
output;
_trt=3;
ETHNICN=3;
_catord=3;
_cat=1;
output;
run;

*-----;
* Merge the _PCT dataset with its frameup dataset(_FRAME) ;
*-----;

proc sort data=_frame3;
  by _datasrt _blkssrt _cat ETHNICN _trt;
run;

proc sort data=_pct3;
  by _datasrt _blkssrt _cat ETHNICN _trt;
run;

```

```

data _pct3;
merge _frame3(in=_inframe) _pct3;
by _datasrt _blcksrt _cat ETHNICN _trt;
if _inframe;
if count=. then
  count=0;
run;

proc sort data=_pct3;
  by _datasrt _blcksrt ETHNICN;
run;

data _miss3(keep=_datasrt _blcksrt ETHNICN totcount);
  set _pct3;
  where ETHNICN=9998;
  retain totcount;
  by _datasrt _blcksrt ETHNICN;

  if first.ETHNICN then
    totcount=0;
  totcount=totcount+count;

  if last.ETHNICN;
run;

data _pct3(drop=totcount);
  merge _pct3 _miss3;
  by _datasrt _blcksrt ETHNICN;

  if totcount=0 then
    delete;
run;

proc sort data=_denomf3;
  by _datasrt _cat;
run;

proc sort data=_denomin3;
  by _datasrt _cat;
run;

data _denomin3;
  merge _denomf3(in=_inframe) _denomin3;
  by _datasrt _cat;

  if _inframe;
  _blcksrt=3;
run;

proc sort data=_pct3;
  by _datasrt _cat;
run;

```

```

data _pct3;
if 0 then
  set basetemplate;
merge _denomin3(in=_a) _pct3;
by _datasrt_cat;

if _a;
  _varname="ETHNICN ";
  _vrlabel="Ethnicity ";
  _rwlable=put(ETHNICN, ethnic.);

if ETHNICN=9998 then
  do;
    _rwlable="Missing ";
    _catord=9998;
  end;
else if ETHNICN=9999 then
  do;
    _rwlable="Total ";
    _catord=9999;
  end;

if _catord=. then
  _catord=9997;
run;

proc sort data=_pct3;
  by _datasrt _blkssrt _catord ETHNICN _trt _cat;
run;

*-----;
* Create _CVALUE variable to display results. ;
* Create _ROWSRT variable to order results. ;
*-----;

data _base3;
length _catlabl $200;
set _pct3 end=eof;
by _datasrt _blkssrt _catord ETHNICN _trt _cat;
retain _rowsrt 0 _rowmax 0;
array _trtcnt(*) _trt1-_trt4;
drop _rowmax _cpct;
length _cpct $100;
_cpct=' ';
_module='mcatstat';

if count > . then
  _cvalue=put(count, 5.);
else
  _cvalue=put(0, 5.);
*-----;
* Format percent to append to display value in _CVALUE ;
*-----;

```

```

if _trt ne . then
  do;

    if _trtcnt(_trt) > 0 then
      do;
        percent=count / _trtcnt(_trt) * 100;

        if percent > 0 then
          do;

            if round(percent, 0.1) GE 0.1 then
              _cpct="(*ESC*){nbspace 1}("||strip(put(percent, 5.1))||")";
            else
              _cpct="(*ESC*){nbspace 1}(0.0)";
              _cvalue=trim(_cvalue)||_cpct;
            end;
          end;
        end;
      end;

/* if length(_cvalue) < 13 then do; */
/* -----; */
/* * Put character A0x at right most character to pad text; */
/* -----; */
/* substr(_cvalue,13,1)= 'A0'x ; */
/* end; */
if first.ETHNICN then
  do;
    _rowsrt=_rowsrt + 1;
    _rowmax=max(_rowsrt, _rowmax);
  end;
_datatyp='data';
_indent=0;
_dptindt=0;
_vorder=1;
_rowjump=1;

if upcase(_rwlable)= '_NONE_' then
  _rwlable=' ';
  _indent=3;
  _dptindt=0;

if _trt=3 +1 then
  _trt=9999;

if eof then
  call symput('_rowsrt', compress(put(_rowmax, 4.)));
  _direct="TOP ";
  _p=2;
run;

data _anal4;
length COUNTRYX $50;
set _data1;

```

```

where same and COUNTRYX is not missing;
    _blkssrt=4;
    _cnt=1;
    _cat=1;

if _trt <=0 then
    delete;
output;
run;

proc sort data=_anal4;
    by _datasrt _blkssrt COUNTRYX _trt _cat;
run;

*--- Counts for each by-sequence, dependant var, and treatment combination ---*;

data _temp4;
    set _anal4;
    output;
run;

proc sort data=_temp4 out=_temp94 nodupkey;
    by _datasrt _blkssrt _cat COUNTRYX _trt USUBJID;
run;

proc freq data=_temp94;
    format COUNTRYX;
    tables _datasrt*_blkssrt*_cat * COUNTRYX *_trt / sparse norow nocol nopercent
        out=_pct4(drop=percent);
run;

proc sort data=_anal4 out=_denom4(keep=_datasrt _cat) nodupkey;
    by _datasrt _cat;
run;

data _denom4;
    set _denom4;
    by _datasrt _cat;
    label count='count';
    _trt=1;
    count=&_trt1;
    output;
    _trt=2;
    count=&_trt2;
    output;
    _trt=3;
    count=&_trt3;
    output;
run;

*-----;
* Create _DENOMF a frame dataset for the denominators ;
*-----;

```

```

data _denomf4;
  _datasrt=1;
  set _bydat1(keep=);
  * All treatment groups ;
  _trt1=0;
  _trt2=0;
  _trt3=0;
  * _CAT is the subgroup variable ;
  _cat=1;
  output;
run;

*-----;
* Transpose _DENOM into _DENOMIN to get COUNT as _TRTn columns ;
*-----;

proc transpose data=_denom4 out=_denomin4(drop=_name__label_) prefix=_trt;
  by _datasrt _cat;
  var count;
  id _trt;
run;

proc sort data=_pct4 out=_expv4 (keep=_datasrt _blcksrt COUNTRYX) nodupkey;
  by _datasrt _blcksrt COUNTRYX;
run;

proc sql noprint;
  select put(nobs - delobs, 12.) into :_nobs from dictionary.tables
    where (libname="WORK" and memname="_PCT4");
  select setting into :miss from dictionary.options where
    upcase(optname)="MISSING";
quit;

proc sort data=_expv4;
  by _datasrt _blcksrt COUNTRYX;
run;

data _frame4;
  set _expv4;
  by _datasrt _blcksrt COUNTRYX;

  if first._blcksrt then
    _catord=0;
    _catord + 1;
    _trt=1;
    _cat=1;
    output;
    _trt=2;
    _cat=1;
    output;
    _trt=3;
    _cat=1;
    output;
run;

```

```

*-----;
* Merge the _PCT dataset with its frameup dataset(_FRAME) ;
*-----;

proc sort data=_frame4;
   by _datasrt _blkssrt _cat COUNTRYX_trt;
run;

proc sort data=_pct4;
   by _datasrt _blkssrt _cat COUNTRYX_trt;
run;

data _pct4;
   merge _frame4(in=_inframe) _pct4;
   by _datasrt _blkssrt _cat COUNTRYX_trt;

   if _inframe;

   if count=. then
      count=0;
run;

proc sort data=_pct4;
   by _datasrt _blkssrt COUNTRYX;
run;

data _miss4(keep=_datasrt _blkssrt COUNTRYX totcount);
   set _pct4;
   where COUNTRYX='ZZZY';
   retain totcount;
   by _datasrt _blkssrt COUNTRYX;

   if first.COUNTRYX then
      totcount=0;
   totcount=totcount+count;

   if last.COUNTRYX;
run;

data _pct4(drop=totcount);
   merge _pct4 _miss4;
   by _datasrt _blkssrt COUNTRYX;

   if totcount=0 then
      delete;
run;

proc sort data=_denomf4;
   by _datasrt _cat;
run;

proc sort data=_denomin4;
   by _datasrt _cat;

```

```

run;

data _denomin4;
    merge _denomf4(in=_inframe) _denomin4;
    by _datasrt _cat;

    if _inframe;
        _blcksrt=4;
run;

proc sort data=_pct4;
    by _datasrt _cat;
run;

data _pct4;
    if 0 then
        set _basetemplate;
    merge _denomin4(in=_a) _pct4;
    by _datasrt _cat;

    if _a;
        _varname="COUNTRYX ";
        _vrlabel="Country ";
        _rwlable=COUNTRYX;

    if COUNTRYX='ZZZY' then
        do;
            _rwlable="Missing ";
            _catord=9998;
        end;
    else if COUNTRYX='ZZZZ' then
        do;
            _rwlable="Total ";
            _catord=9999;
        end;
    if _catord=. then
        _catord=9997;
run;

proc sort data=_pct4;
    by _datasrt _blcksrt _catord COUNTRYX _trt _cat;
run;

*-----;
* Create _CVALUE variable to display results. ;
* Create _ROWSRT variable to order results. ;
*-----;

data _base4;
    length _catlabl $200;
    set _pct4 end=eof;
    by _datasrt _blcksrt _catord COUNTRYX _trt _cat;
    retain _rowsrt 0 _rowmax 0;

```

```

array _trtcnt(*) _trt1-_trt4;
drop _rowmax _cpct;
length _cpct $100;
_cpct='';
_module='mcatstat';

if count > . then
  _cvalue=put(count, 5.);
else
  _cvalue=put(0, 5.);
*-----;
* Format percent to append to display value in _CVALUE ;
*-----;

if _trt ne . then
  do;

    if _trtcnt(_trt) > 0 then
      do;
        percent=count / _trtcnt(_trt) * 100;

        if percent > 0 then
          do;

            if round(percent, 0.1) GE 0.1 then
              _cpct="(*ESC*){nbspace 1}("||strip(put(percent, 5.1))||")";
            else
              _cpct="(*ESC*){nbspace 1}(0.0)";
            _cvalue=trim(_cvalue)||_cpct;
          end;
        end;
      end;
    end;

if length(_cvalue) < 13 then
  do;
    *-----;
    * Put character A0x at right most character to pad text;
    *-----;
    substr(_cvalue, 13, 1)='A0'x;
  end;

if first.COUNTRYX then
  do;
    _rowsrt=_rowsrt + 1;
    _rowmax=max(_rowsrt, _rowmax);
  end;
_datatyp='data';
_indent=0;
_dptindt=0;
_vorder=1;
_rowjump=1;

if upcase(_rwlable)= '_NONE_' then
  _rwlable=' ';

```

```

_indent=3;
_dptindt=0;

if _trt=3 +1 then
    _trt=9999;

if eof then
    call symput('_rowsrt', compress(put(_rowmax, 4.)));
    _direct="TOP ";
    _p=2;
run;

data _anal5;
length COMBODFLNX 8;
set _data1;
where same and COMBODFLNX is not missing;
_blktsrt=5;
_cnt=1;
_cat=1;

if _trt <=0 then
    delete;
output;
run;

proc sort data=_anal5;
    by _datasrt _blktsrt COMBODFLNX _trt _cat;
run;

*--- Counts for each by-sequence, dependant var, and treatment combination ---*;

data _temp5;
    set _anal5;
    output;
run;

proc sort data=_temp5 out=_temp95 nodupkey;
    by _datasrt _blktsrt _cat COMBODFLNX _trt USUBJID;
run;

proc freq data=_temp95;
    format COMBODFLNX;
    tables _datasrt*_blktsrt*_cat * COMBODFLNX *_trt / sparse norow nocol
        nopercent out=_pct5(drop=percent);
run;

proc sort data=_anal5 out=_denom5(keep=_datasrt _cat) nodupkey;
    ;
    by _datasrt _cat;
run;

data _denom5;
    set _denom5;
    by _datasrt _cat;

```

```

label count='count';
_trt=1;
count=&_trt1;
output;
_trt=2;
count=&_trt2;
output;
_trt=3;
count=&_trt3;
output;
run;

data _denomf5;
.datasrt=1;
set _bydat1(keep=);
* All treatment groups ;
_trt1=0;
_trt2=0;
_trt3=0;
*_CAT is the subgroup variable ;
_cat=1;
output;
run;

proc transpose data=_denom5 out=_denomin5(drop=_name__label_) prefix=_trt;
by _datasrt _cat;
var count;
id _trt;
run;

proc sql noprint;
select count(distinct COMBODFLNX) into :totexpv from _anal5;
select distinct COMBODFLNX , COMBODFLX into :expv1 - :expv2 ,
:catlab1 - :catlab2 from _anal5 order by COMBODFLNX;
quit;

data _frame5;
.datasrt=1;
set _bydat1(keep=);
blcksrt=5;
length COMBODFLNX 8;
length _catLabl $50;
_catLabl=' ';
_catLabl="Yes ";
_trt=1;
COMBODFLNX=1;
_catord=1;
_cat=1;
output;
_trt=2;
COMBODFLNX=1;
_catord=1;
_cat=1;
output;

```

```

_trt=3;
COMBODFLNX=1;
_catord=1;
_cat=1;
output;
_catLabl="No ";
_trt=1;
COMBODFLNX=2;
_catord=2;
_cat=1;
output;
_trt=2;
COMBODFLNX=2;
_catord=2;
_cat=1;
output;
_trt=3;
COMBODFLNX=2;
_catord=2;
_cat=1;
output;
run;

proc sort data=_frame5;
   by _datasrt _blkssrt _cat COMBODFLNX _trt;
run;

proc sort data=_pct5;
   by _datasrt _blkssrt _cat COMBODFLNX _trt;
run;

data _pct5;
   merge _frame5(in=_inframe) _pct5;
   by _datasrt _blkssrt _cat COMBODFLNX _trt;
   if _inframe;
   if count=. then
      count=0;
run;

proc sort data=_pct5;
   by _datasrt _blkssrt COMBODFLNX;
run;

data _miss5(keep=_datasrt _blkssrt COMBODFLNX totcount);
   set _pct5;
   where COMBODFLNX=9998;
   retain totcount;
   by _datasrt _blkssrt COMBODFLNX;
   if first.COMBODFLNX then
      totcount=0;
   totcount=totcount+count;

```

```

if last.COMBODFLNX;
run;

data _pct5(drop=totcount);
  merge _pct5 _miss5;
  by _datasrt _blcksrt COMBODFLNX;

  if totcount=0 then
    delete;
run;

proc sort data=_denomf5;
  by _datasrt _cat;
run;

proc sort data=_denomin5;
  by _datasrt _cat;
run;

data _denomin5;
  merge _denomf5(in=_inframe) _denomin5;
  by _datasrt _cat;

  if _inframe;
  _blcksrt=5;
run;

proc sort data=_pct5;
  by _datasrt _cat;
run;

data _pct5;
  if 0 then
    set basetemplate;
  merge _denomin5(in=_a) _pct5;
  by _datasrt _cat;

  if _a;
  _varname="COMBODFLNX ";
  _vrlabel="Comorbidities(*ESC*){super c} ";
  _rlabel=_catLabl;

  if COMBODFLNX=9998 then
    do;
      _rlabel="Missing ";
      _catord=9998;
    end;
  else if COMBODFLNX=9999 then
    do;
      _rlabel="Total ";
      _catord=9999;
    end;
end;

```

```

if _catord=. then
    _catord=9997;
run;

proc sort data=_pct5;
    by _datasrt _blkssrt _catord COMBODFLNX _trt _cat;
run;

data _base5;
    length _catlbl $200;
    set _pct5 end=eof;
    by _datasrt _blkssrt _catord COMBODFLNX _trt _cat;
    retain _rowsrt 0 _rowmax 0;
    array _trtcnt(*) _trt1-_trt4;
    drop _rowmax _cpct;
    length _cpct $100;
    _cpct=':';
    _module='mcatstat';

if count > . then
    _cvalue=put(count, 5.);
else
    _cvalue=put(0, 5.);

if _trt ne . then
    do;

        if _trtcnt(_trt) > 0 then
            do;
                percent=count / _trtcnt(_trt) * 100;

                if percent > 0 then
                    do;

                        if round(percent, 0.1) GE 0.1 then
                            _cpct="(*ESC*){nbspace 1}("||strip(put(percent, 5.1))||")";
                        else
                            _cpct="(*ESC*){nbspace 1}(0.0)";
                            _cvalue=trim(_cvalue)||_cpct;
                    end;
                end;
            end;
        end;

if length(_cvalue) < 13 then
    do;
        *-----;
        * Put character A0x at right most character to pad text;
        *-----;
        substr(_cvalue, 13, 1)='A0'x;
    end;

if first.COMBODFLNX then
    do;
        _rowsrt=_rowsrt + 1;

```

```

        _rowmax=max(_rowsrt, _rowmax);
    end;
_datatyp='data';
_indent=0;
_dptindt=0;
_vorder=1;
_rowjump=1;

if upcase(_rwlable)= '_NONE_ ' then
    _rwlable=' ';
_indent=3;
_dptindt=0;

if _trt=3 +1 then
    _trt=9999;

if eof then
    call symput('_rowsrt', compress(put(_rowmax, 4.)));
    _direct="TOP ";
    _p=2;
run;

data _anal6;
length OBSCATFN 8;
set _data1;
where same and OBSCATFN is not missing;
_blkssrt=6;
_cnt=1;
_cat=1;

if _trt <=0 then
    delete;
output;
run;

proc sort data=_anal6;
    by _datasrt _blkssrt OBSCATFN _trt _cat;
run;

*--- Counts for each by-sequence, dependant var, and treatment combination ---*;

data _temp6;
set _anal6;
output;
run;

proc sort data=_temp6 out=_temp96 nodupkey;
    by _datasrt _blkssrt _cat OBSCATFN _trt USUBJID;
run;

proc freq data=_temp96;
format OBSCATFN;
tables _datasrt*_blkssrt*_cat * OBSCATFN * _trt / sparse norow nocol nopercnt
      out=_pct6(drop=percent);

```

```

run;

proc sort data=_anal6 out=_denom6(keep=_datasrt_cat) nodupkey;
   by _datasrt_cat;
run;

data _denom6;
   set _denom6;
   by _datasrt_cat;
   label count='count';
   _trt=1;
   count=&_trt1;
   output;
   _trt=2;
   count=&_trt2;
   output;
   _trt=3;
   count=&_trt3;
   output;
run;

data _denomf6;
   _datasrt=1;
   set _bydat1(keep=);
   * All treatment groups ;
   _trt1=0;
   _trt2=0;
   _trt3=0;
   * _CAT is the subgroup variable ;
   _cat=1;
   output;
run;

proc transpose data=_denom6 out=_denomin6(drop=_name__label_) prefix=_trt;
   by _datasrt_cat;
   var count;
   id _trt;
run;

proc sql noprint;
   select count(distinct OBSCATFN) into :totexpv from _anal6;
   select distinct OBSCATFN , OBSCATFL into :expv1 - :expv2 , :catlab1 - :catlab2
      from _anal6 order by OBSCATFN;
quit;

data _frame6;
   _datasrt=1;
   set _bydat1(keep=);
   _blkrsrt=6;
   length OBSCATFN 8;
   length _catLabl $50;
   _catLabl=' ';
   _catLabl="Yes ";
   _trt=1;

```

```

OBSCATFN=1;
_catord=1;
_cat=1;
output;
_trt=2;
OBSCATFN=1;
_catord=1;
_cat=1;
output;
_trt=3;
OBSCATFN=1;
_catord=1;
_cat=1;
output;
_catLabl="No ";
_trt=1;
OBSCATFN=2;
_catord=2;
_cat=1;
output;
_trt=2;
OBSCATFN=2;
_catord=2;
_cat=1;
output;
_trt=3;
OBSCATFN=2;
_catord=2;
_cat=1;
output;
run;

proc sort data=_frame6;
   by _datasrt _blkssrt _cat OBSCATFN _trt;
run;

proc sort data=_pct6;
   by _datasrt _blkssrt _cat OBSCATFN _trt;
run;

data _pct6;
   merge _frame6(in=_inframe) _pct6;
   by _datasrt _blkssrt _cat OBSCATFN _trt;
   if _inframe;
   if count=. then
      count=0;
run;

proc sort data=_pct6;
   by _datasrt _blkssrt OBSCATFN;
run;

```

```
data _miss6(keep=_datasrt _blcksrt OBSCATFN totcount);
  set _pct6;
  where OBSCATFN=9998;
  retain totcount;
  by _datasrt _blcksrt OBSCATFN;
```

```
  if first.OBSCATFN then
    totcount=0;
  totcount=totcount+count;
```

```
  if last.OBSCATFN;
```

```
run;
```

```
data _pct6(drop=totcount);
  merge _pct6 _miss6;
  by _datasrt _blcksrt OBSCATFN;
```

```
  if totcount=0 then
    delete;
```

```
run;
```

```
proc sort data=_denomf6;
  by _datasrt _cat;
run;
```

```
proc sort data=_denomin6;
  by _datasrt _cat;
run;
```

```
data _denomin6;
  merge _denomf6(in=_inframe) _denomin6;
  by _datasrt _cat;

  if _inframe;
  _blcksrt=6;
run;
```

```
proc sort data=_pct6;
  by _datasrt _cat;
run;
```

```
data _pct6;
  if 0 then
    set _basetemplate;
  merge _denomin6(in=_a) _pct6;
  by _datasrt _cat;

  if _a;
  _varname="OBSCATFN ";
  _vrlabel="Obese(*ESC*){super d} ";
  _rwlable=_catLabl;

  if OBSCATFN=9998 then
    do;
```

```

_rwlabel="Missing ";
_catord=9998;
end;
else if OBSCATFN=9999 then
do;
    _rwlabel="Total ";
    _catord=9999;
end;

if _catord=. then
    _catord=9997;
run;

proc sort data=_pct6;
    by _datasrt _blkssrt _catord OBSCATFN _trt _cat;
run;

data _base6;
length _catlbl $200;
set _pct6 end=eof;
by _datasrt _blkssrt _catord OBSCATFN _trt _cat;
retain _rowsrt 0 _rowmax 0;
array _trtcnt(*) _trt1-_trt4;
drop _rowmax _cpct;
length _cpct $100;
_cpct='';
_module='mcatstat';

if count > . then
    _cvalue=put(count, 5.);
else
    _cvalue=put(0, 5.);

if _trt ne . then
do;

    if _trtcnt(_trt) > 0 then
        do;
            percent=count / _trtcnt(_trt) * 100;

            if percent > 0 then
                do;

                    if round(percent, 0.1) GE 0.1 then
                        _cpct="(*ESC*){nbspace 1}("||strip(put(percent, 5.1))||")";
                    else
                        _cpct="(*ESC*){nbspace 1}(0.0)";
                    _cvalue=trim(_cvalue)||_cpct;
                end;
            end;
        end;
    end;

if length(_cvalue) < 13 then
do;

```

```

*-----;
* Put character A0x at right most character to pad text;
*-----;
substr(_cvalue, 13, 1)='A0'x;
end;

if first.OBSCATFN then
  do;
    _rowsrt=_rowsrt + 1;
    _rowmax=max(_rowsrt, _rowmax);
  end;
_datatyp='data';
_indent=0;
_dptindt=0;
_vorder=1;
_rowjump=1;

if upcase(_rwlable)= '_NONE_' then
  _rwlable=' ';
_indent=3;
_dptindt=0;

if _trt=3 +1 then
  _trt=9999;

if eof then
  call symput('_rowsrt', compress(put(_rowmax, 4.)));
  _direct="TOP ";
  _p=2;
run;

*****;
*SPECIFICATION 7 -1) Age - descriptive statistics *;
*****;

data _anal7;
  set _data1;
  where _trt > 0;
  _blcksrt=7;
  output;
run;

*-----;
* Make sure data is sorted by groups ;
*-----;

proc sort data=_anal7;
  by _datasrt _blcksrt _trt;
run;

*-----;
* Call PROC UNIVARIATE to generate all possible statistics plus any ;
* Percentiles or Confidence Intervals. ;
*-----;

```

```

proc univariate data=_anal7 noprint;
  by _datasrt _blcksrt _trt;
  var AGETR01;
  output out=_msum7 CSS=CSS CV=CV KURTOSIS=KURTOSIS MAX=MAX MEAN=MEAN N=N
        MIN=MIN MODE=MODE RANGE=RANGE NMISS=NMISS NOBS=NOBS STDMEAN=STDMEAN
        SKEWNESS=SKEWNESS STD=STD USS=USS SUM=SUM VAR=VAR MEDIAN=MEDIAN P1=P1
P5=P5
  P10=P10 P90=P90 P95=P95 P99=P99 Q1=Q1 Q3=Q3 QRANGE=QRANGE GINI=GINI MAD=MAD
  QN=QN SN=SN STD_GINI=STD_GINI STD_MAD=STD_MAD STD_QN=STD_QN
  STD_QRANGE=STD_QRANGE STD_SN=STD_SN NORMAL=NORMAL PROBN=PROBN
MSIGN=MSIGN
  PROBM=PROBM SIGNRANK=SIGNRANK PROBS=PROBS T=T PROBT=PROBT;
run;

*-----;
*Create Frame dataset when user requested Subgrouping as well as set;
*sparsesgrpyn to Y to sparse subgrp categories of a format. ;
*-----;

data _frame7;
  set _bydat1(keep=);
  _datasrt=1;
  _blcksrt=7;
  _catord=1;
  _trt=1;
  _cat=1;
  output;
  _trt=2;
  _cat=1;
  output;
  _trt=3;
  _cat=1;
  output;
run;

proc sort data=_frame7;
  by _datasrt _blcksrt _trt;
run;

data _msum7;
  merge _msum7 _frame7;
  by _datasrt _blcksrt _trt;
run;

*-----;
* Generate _result1 from OUT= dataset of PROC UNIVARIATE ;
*-----;

data _result1_7;
  if 0 then
    set _basetemplate;
  set _msum7 end=eof;
  _rowsrt=0 + 1;

```

```

_rwlabel="Mean (SD) ";
_cvalue=' ';
_nvalue=.;
*-----;
* MEAN(STD) ;
*-----;

if mean ne . and std ne . then
  do;
    _cValue=strip(put(mean, 5.1) ) || '(' || strip(put(std, 5.2) ) || ')';
  end;
else if mean eq . then
  _cValue="-" || '(' || "-" || ')';
else if std eq . then
  do;
    _cValue=strip(put(mean, 5.1) ) || '(' || "NE" || ')';
  end;
output;
_rowsrt=0 + 2;
_rwlabel="Median ";
_cvalue=' ';
_nvalue=.;
_nvalue=MEDIAN;

if MEDIAN ne . then
  _cValue=strip(put(MEDIAN, 5.1) );
else
  _cValue="-";
output;
_rowsrt=0 + 3;
_rwlabel="Min, max ";
_cvalue=' ';
_nvalue=.;
*-----;
* MINMAX MINMAXC MEDIAN(MINMAX) MEDIAN(MINMAXC) ;
*-----;
_cValue='';

if min ^=. & max ^=. then
  do;
    _cValue=trim(_cvalue) || '(' || strip(put(min, 5.0)
      )|| ',' || strip(put(max, 5.0) )|| ')';
  end;
else if min=. & max=. then
  do;
    _cValue=trim(_cvalue) || '(' || "-" || ',' || "-" || ')';
  end;
_cValue=compb1(_cValue);
output;
run;

*-----;
* Generate _logresult1 from OUT= dataset of PROC UNIVARIATE for log stats;
*-----;

```

```

data _logresult1_7;
  if 0 then
    set _basetemplate;
    stop;
run;

*-----;
* Generate _result2 from confidence interval output dataset ;
*-----;

data _result2_7;
  if 0 then
    set _basetemplate;
    stop;
run;

*-----;
* Generate _logresult2 from confidence interval output dataset for log stats;
*-----;

data _logresult2_7;
  if 0 then
    set _basetemplate;
    stop;
run;

*-----;
* Combine to form one result dataset. Set variables that do not depend ;
* on the statistic. Sort the result. ;
*-----;

data _base7;
  set _result1_7 _result2_7 _logresult1_7 _logresult2_7;

  if _trt=4 then
    _trt=9999;
  _varname="AGETR01";
  _vrlabel="Age at vaccination (years) ";
  _datatyp='data';
  _module='msumstat';
  _indent=3;
  _rowjump=1;
  _dptindt=0;
run;

*-----;
* merge ISAM subgroup variables _SUBCAT _COLABEL ;
*-----;

proc sort data=_base7;
  by _datasrt _blkssrt _rowsrt;
run;

```

```

data _final;
  set _base1 _base2 _base3 _base4 _base5 _base6 _base7;
run;

proc sort data=_final;
  by _datasrt _blkssrt _rowsrt;
run;

*-----;
* At least one of TRT and STAT is vertical;
*-----;

data _final;
  set _final;
  drop __trt;

  if __trt=9999 then
    __trt=3 + 1;
  else
    __trt=__trt;

  if __trt=. then
    __trt=1;
  _column=__trt;

  if _column=9999 then
    _column=3 + 1;
run;

proc sort data=_final out=_final;
  by _datasrt _blkssrt _rowsrt _column;
run;

data _linecnt;
  set _final end=eof;
  by _datasrt _blkssrt _rowsrt _column;
  retain _totline _maxval _maxrow _rwlbttag _vrlbttag 0 _maxline _linecnt;
  keep _datasrt _blkssrt _totline _linecnt _maxrow;

  if _rowjump=. then
    _rowjump=1;

  if first._blkssrt then
    do;
      *-----;
      * Count words inside DATA step ;
      *-----;
      _token=repeat(' ', 99);
      _count=1;
      _token=scan(_vrlabel, _count, "|");

      if _token=:_ then
        _tag=1;
      else

```

```

_tag=0;

do while(_token ^= ' ');
  _count=_count + 1;
  _token=scan(_vrlabel, _count, "|");
end;
_linecnt=_count - 1 + _tag;
_totline=_linecnt;

if _vrlabel ne '' and _vrlabel ne '^' & _datatyp='data' then
  _vrlbtag=1;
end;

if first._rowsrt then
  do;
    *-----;
    * Count words inside DATA step ;
    *-----;
    _token=repeat(' ', 99);
    _count=1;
    _token=scan(_rwlable, _count, "|");

    if _token=:_ then
      _tag=1;
    else
      _tag=0;

    do while(_token ^= ' ');
      _maxrow=max(_maxrow, length(_token) + _indent);
      _count=_count + 1;
      _token=scan(_rwlable, _count, "|");
    end;
    _maxline=_count - 1 + _tag;

    if _rwlable ne '' then
      _rwlbtag=1;
      _totline + _rowjump - 1;
    end;
  *-----;
  * Count words inside DATA step ;
  *-----;
  _token=repeat(' ', 99);
  _count=1;
  _token=scan(_cvalue, _count, "|");

  if _token=:_ then
    _tag=1;
  else
    _tag=0;

  do while(_token ^= ' ');
    _maxval=max(_maxval, length(_token));
    _count=_count + 1;
    _token=scan(_cvalue, _count, "|");

```

```

end;
_ccnt=_count - 1 + _tag;
_maxline=max(_maxline, _ccnt);

if last._rowsrt then
    _totline=_maxline + _totline;

if last._blktsrt then
    do;
        _totline=_totline - _rowjump + 1;
        output;
    end;

if eof then
    do;
        call symput('_valwid', compress(put(_maxval, 3.)));
        call symput('_rwlbtags', put(_rwlbtags, 1.));
        call symput('_vrlbtags', put(_vrlbtags, 1.));
    end;
run;

data _final;
length _direct $20;
_direct=' ';
merge _final _linecnt;
by _datasrt _blktsrt;
run;

proc sql noprint;
create table rson as select distinct _trt, _column , _vrlabel as _rwlable ,
    _datasrt, _blktsrt, (min(_rowsrt)-0.5) as _rowsrt , _dptindt as _indent , 0
    as _dptindt from _final(where=(_vrlabel^='')) group by _trt, _column ,
    _datasrt, _blktsrt, _vrlabel;
quit;

data ADSL_DEMO_7D_PEDS_EVAL_EFF;
length _rvalue $800;
set _final rson end=eof;
_rwindt=sum(_indent, _dptindt);

if _rwindt <=0 then
    _rvalue=_rwlable;

/* else _rvalue=repeat(byte(160),_rwindt-1)||_rwlable; */
else
    _rvalue=repeat("~{nbspace 1}", _rwindt-1)||_rwlable;
_dummy=1;

if _trt=. then
    _trt=1;
run;

proc sort data=ADSL_DEMO_7D_PEDS_EVAL_EFF;
by _datasrt _trt _blktsrt _rowsrt;

```

```

run;

data treat;
length FMTNAME $8 start 8 label $200;
fmtname='TREAT';

do start=1 to 3 + ("N"="Y");
    label=symget('_TRTLB'|| compress(put(start, 4.)));
    label=trim(label)
        || "|| (N~{super a}=" || compress(symget("_TRT" || compress(put(start,
4.)))) || ")"
        || "|n~{super b} (%)";
    output;
end;
run;

proc format cntlin=treat;
run;

options orientation=LANDSCAPE papersize="LETTER";
ods escapechar="~";
title1 "Demographic Characteristics (*ESC*){unicode 2013} Blinded Placebo-Controlled Follow-up Period (*ESC*)
{unicode 2013} ";
title2 "Subjects 12 Through 15 Years of Age and Without Evidence of Infection Prior to 7 Days After Dose 2 (*ESC*)
{unicode 2013} ";
title3 "Evaluable Efficacy (7 Days) Population ";
footnote1 "a.(*ESC*){nbspce 5}N = number of subjects in the specified group, or the total sample. This value is the
denominator for the percentage calculations. ";
footnote2 "b.(*ESC*){nbspce 5}n = Number of subjects with the specified characteristic. ";
footnote3 "c.(*ESC*){nbspce 5}Number of subjects who have 1 or more comorbidities that increase the risk of severe
COVID-19 disease: defined as subjects who had at least one of the Charlson comorbidity index category or BMI
(*ESC*){unicode 2265}95(*ESC*){super th} percentile. ";
footnote4 "d.(*ESC*){nbspce 5}Obese is defined as BMI (*ESC*){unicode 2265}95(*ESC*){super th} percentile
from the growth chart. Refer to the CDC growth charts at
https://www.cdc.gov/growthcharts/html\_charts/bmiagerev.htm. ";

data outdata1;
    set ADSL_DEMO_7D_PEDS_EVAL_EFF;

    if upcase(_module)='MCATSTAT' then
        _cvalue=transtrn(compress(_cvalue), '(', ')');
    _fixvar=1;
    _fix2var=1;
run;

option nobyline;

proc sort data=outdata1;
    by _datasrt_trt _blkssrt _rowsrt;
run;

proc sql noprint;
    select distinct start, label into :start1, :_trlbl1 - :_trlbl99 from treat
        order by start;

```

```

quit;

proc sort data=outdata1 out=_pre_transposed;
    by _fixvar _fix2var _datasrt _blkssrt _rowsrt _rvalue _trt;
run;

data _pre_transposed;
    set _pre_transposed;

    if _trt=9999 then
        _trt=3 +1;
run;

proc transpose data=_pre_transposed out=_column_transposed (drop=_name_)
    prefix=TRT;
    by _fixvar _fix2var _datasrt _blkssrt _rowsrt _rvalue;
    var _cvalue;
    id _trt;
run;

ods html file="&outtable./";

data REPORT;
    set _column_transposed;
    _dummy=1;
run;

proc sort data=report;
    by _datasrt _blkssrt _rowsrt _dummy;
run;

proc report data=report nowd list missing contents="" split="|" spanrows
    style(report)={} style(header)={} style(column)={};
    column _fixvar _fix2var _datasrt _blkssrt _rowsrt ("" _rvalue)
        (("Vaccine Group (as Randomized)~{line}" TRT1 TRT2) TRT3 _dummy);
    define _fixvar / group noprint;
    define _fix2var / group noprint;
    define _datasrt / group order=internal noprint;
    define _blkssrt / group order=internal noprint;
    define _rowsrt / group order=internal noprint;
    define _rvalue / group id " " order=data style(column)={just=left width=60mm
        rightmargin=18px} style(header)={just=left} left;
    define _dummy / sum noprint;
    define TRT1 / group nozero "&_trlbl1." spacing=2 style(column)={width=35mm
        leftmargin=12px} style(header)={just=center} center;
    define TRT2 / group nozero "&_trlbl2." spacing=2 style(column)={width=35mm
        leftmargin=12px} style(header)={just=center} center;
    define TRT3 / group nozero "&_trlbl3." spacing=2 style(column)={width=35mm
        leftmargin=12px} style(header)={just=center} center;
    break before _fixvar / contents="" page;
    compute before _fix2var;
        line @1 "~n ";
    endcomp;
    compute after _blkssrt;

```

```
    line " ~n ";
endcomp;
run;
```

```
ods HTML close;
```

```
proc printto;
run;
```